



# PRODUCT DATA SHEET

## WATERPROOFING PRIMER

### Description

A blend of selected asphalts and petroleum cutback conforming to the requirements of a damproofing/waterproofing primer PCGSB.37.GP.9. Penetrating primer formulated for brush or spray applications.

### Recommended use

A surface conditioner to enhance bond between substrate and waterproofing membrane or other asphaltic type coatings. Used as a damproofing/waterproofing coating to prevent migration of moisture through masonry or concrete structures.

### Applicable Specifications

- Ambient temperature. Viscosity of product increases at lower temperatures.

### Application Guidelines

All surfaces to be clean, dry and free of deleterious material. Surface should be relatively smooth and free of irregularities. Any surface irregularities should be parged to a smooth consisted surface.

### Coverage

- Surface Conditioning/Priming – 0.1 - 0.2 litres/m<sup>2</sup>

### Packaging

- 23 litre pail
- 205 litre drum

## **WATERPROOFING PRIMER**

<b>PROPERTIES</b>	<b>TEST METHODS</b>	<b>TYPICAL RESULTS</b>
Flash Point	ASTM D-1310 Min 20°C	26.7°C
Water Content	CGSB-37-GP-9M ASTM D-95 Max. 1.0%	0%
Distillation to 360°C	CGSB-37-GP-9M ASTM D-402 Min. 25% Min. 70% Min. 85% Min. 92%	71.7% 86.8% 91.8% 96.2%
% Residue by volume to 360°C	Min. 50: Max. 75	60.2
Tests on Residue Penetration @ 25°C	CGSB-37-GP-9M ASTM D-5 Min. 35: Max. 85	50
Softening Point	CGSB-37-GP-9M ASTM D-2398 Min. 49°C: Max. 80°C	54.5
Solubility	CGSB-37-GP-9M ASTM D-2042 Min. 98%	99.96%

**McAsphalt Industries Ltd.**  
 8800 Sheppard Avenue East  
 Scarborough, Ontario M1B 5R4  
 Tel: (416) 281-8181 Fax: (416) 281-8842  
 Email: mcasys@idirect.com



# Material Safety Data Sheet

## Waterproofing Primer

### 1. PRODUCT SUPPLIER/MSDS PREPARATION INFORMATION

**Product Manufacturer /Supplier:** McAsphalt Industries Ltd.  
8800 Sheppard Ave. East  
Scarborough, Ontario  
M1B 5R4  
(416) 281-8181      **MSDS Prepared By:** Operations Dept.

**Product:** Waterproofing Prime, Waterproofing Primer  
**Product Use:** Water Proofing

**Revision Date:** February 8, 2010      **Supersedes:** January 18, 2006

**EMERGENCY NUMBER:** CANUTEC – (613) 996-6666

**WHMIS:** B2-Flammable Liquid, D2B – Toxic Material

**Transportation of Dangerous Goods:** UN 1999 Tars, Liquid Class 3, PGII - Flammable Liquid

**Workplace Label:** Health-2 Fire-3 Reactivity – 0 Personal Protection – P (Compliance Centre)

### 2. INGREDIENTS / COMPOSITION

COMPONENT(S)	CAS #	% (w/w)	LD <sub>50</sub>	LC <sub>50</sub>	PIN
Asphalt	8052-42-4	25-50	N/A	N/A	N/A
Solvent(Naptha)	64742-48-9	60-100	N/A	N/A	UN 1255

For in-situ solvent ingredients see section 6

### 3. PHYSICAL DATA

<b>Physical State:</b> Liquid	<b>Appearance:</b> Black
<b>Specific Gravity:</b> 0.9-1.0@ 15°C	<b>Odour:</b> Tar/solvent odour
<b>Freezing Point:</b> N/Av	<b>Odour Threshold:</b> N/Av
<b>Boiling Point:</b> 160°C	<b>Solubility:</b> Not water soluble
<b>Vapour Pressure:</b> 10kpa@20°C	<b>Evaporation Rate:</b> N/Av
<b>Vapour Density:</b> 3-4 (air=1)	<b>pH:</b> N/Av

### 4. FIRE & EXPLOSION HAZARD

**Flash Point & Method:** 10°C PMCC      **Flammability Limits:** unknown  
**Auto-Ignition Temperature:** Not determined      Estimate - LEL 0.8% UEL 6.0%

**Fire Fighting Media:** CO<sub>2</sub>, Dry Chemical, Water spray with caution

**Explosion/Flammability:** Eliminate sources of ignition, (ie flames/sparks) may be sensitive to static discharge

**Hazardous Combustion Products:** CO, NO<sub>x</sub>, SO<sub>x</sub>, sulfur products

**THIS PRODUCT IS EXTREMELY FLAMMABLE!!**  
**USE CAUTION WHEN HANDLING ANY CONTAINERS(INCLUDING EMPTY)**  
**THEY MAY CONTAIN EXPLOSIVE AIR/SOLVENT MIXTURES.**

## 5. REACTIVITY DATA

**Stability:** Stable

**Incompatible Materials:** Water, Strong Oxidizers

**Conditions of Reactivity:** N/A

**Hazardous Decomposition Products:** CO, SO<sub>x</sub>, NO<sub>x</sub>, other Sulfur compounds

**Synergistic Products:** None

## 6. HEALTH HAZARD INFORMATION

**Skin:** can cause skin irritation, dermatitis. Skin defatting with chronic exposure

**Eyes:** yes – irritation, can cause conjunctivitis

**Inhalation:** yes, irritation of nose, respiratory tract, nausea, headaches

**Exposure Limits:** *Always check local regulations*

Compound	CAS #	Exposure Limit (TWA)	% of Waterproofing Primer
Asphalt Fume	8052-42-4	5mg/M <sup>3</sup>	
Petroleum Distillates		100 PPM	
Benzene	71-43-2	1 ppm	0.28% approx
Xylene	1330-20-7	100 ppm	2.18 % approx
Hexane	110-54-3	50 ppm	1.04 % approx
Cyclohexane	110-54-3	300 ppm (NIOSH)	1.45% approx
Toluene	108-88-3	100 ppm	1.03% approx

Contains benzene, a known carcinogen.

Use **extra caution in confined spaces**, ensure adequate ventilation to limit exposure

**Ingestion:** yes, - (ingestion unlikely) do not induce vomiting.

## 7. PREVENTATIVE MEASURES

**Personal Protective Equipment:** Rubber gloves, goggles, face shield, respirator with organic vapour cartridge

**Handling/Shipping/Storage:** **Do not cut or weld on or near empty/full containers!**

Flammable/explosive vapours may be present in all containers including empty containers.

Do not store near flames or heat. No Smoking.

Ground containers when transferring.

**Ventilation:** Ensure adequate ventilation, to limit exposure & remove flammable vapours

**Disposal:** See appropriate federal, provincial, municipal regulations

**LEAKS AND SPILLS:** Contain with earth or sand, allow to cool and harden. Eliminate sources of ignition. Notify authorities when in water, or large spills.

## 8. FIRST AID

**SKIN:** Wash with soap and water, if irritation persists, seek medical aid

**EYES:** Gently flush with lots of water. Seek Medical Help.

**INHALATION:** Remove victim to fresh air. Seek Medical Help.

**INGESTION:** Give lots of water to drink. Seek Medical Help.

## 9. NOTE

The information contained herein relates only to this product or material and may not be valid when used in combination with any other product or material or in any process. If the process is not to be used under conditions, which are normal or reasonably foreseeable, this information cannot be relied upon as complete or applicable. The information contained herein is based upon the information available at the indicated date of preparation, the above supplier assumes no liability whatsoever for the accuracy or completeness of the information.